


Data sheet | Item number: 2273-204

COMPACT PUSH WIRE® connector for junction boxes; 4-conductor terminal block; transparent housing; red cover

www.wago.com/2273-204



Data

Electrical data

Ratings per	IEC/EN 60664-1
Rated voltage (II / 2)	450 V
Rated impulse voltage (II / 2)	4 kV
Rated current	24 A
Legend (ratings)	(II / 2) ≙ Overvoltage category II / Pollution degree 2



Connection data

Connection technology	PUSH WIRE®
Actuation type	Push-in
Connectable conductor materials	Copper
Solid conductor	0.5 ... 2.5 mm ² / 18 ... 14 AWG
Strip length	11 mm / 0.43 Inch
Total number of connection points	4
Total number of potentials	1
Type of wiring	Side-entry wiring

Geometrical Data

Width	18 mm / 0.709 Inch
Height	5.8 mm / 0.228 Inch
Depth	16.7 mm / 0.657 Inch

Material Data

Color	red
Cover color	red
Flammability class per UL94	V2
Fire load	0.025 MJ
Weight	1.3 g


Environmental Requirements

Ambient temperature (operation)	60 °C
Continuous operating temperature up to	105 °C
T-Marking per EN 60998	T60

Commercial data

Packaging type	BOX
Country of origin	DE
GTIN	4050821027867
Customs Tariff No.	85369010000
Product Group	7 (Push Wire Conn.)

Country specific Approvals

Logo	Approval	Certificate name
	VDE VDE Prüf- und Zertifizierungsinstitut	40029794

Ship Approvals

Logo	Approval	Certificate name
	ABS American Bureau of Shipping	15-HG1419918-PDA

Subject to changes.